## **RESPIRATORY GEAR**

### P2 DISPOSABLE RESPIRATOR WITH VALVE & ACTIVE CARBON FILTER

PRODUCT DATA SHEET: PC531



PRODUCT CODE:









### **FEATURES AND BENEFITS**

- P2: Certified to AS/NZS 1716:2012 Respiratory Protective Devices
- Therapeutic Goods Administration (TGA) Listed
- P2 activated carbon disposable respirator for protection against nuisance level organic vapours, mechanically and thermally generated particles
- Lightweight cupped design for comfortable extended wear
- Dual Quicklock head strap for ease of donning and doffing
- ProValve exhalation valve for decreased breathing resistance and heat stress
- Nose flange for increased protection and facial fit
- Resealable bag for hygienic storage

### **AVAILABLE IN**

PRODUCT CODE	QUANTITY	CARTON
PC531-3	3 pieces	30 packs
PC531	12 pieces	20 boxes

### **PRODUCT DETAILS**

Straps: Latex-Free Rubber Band Filter Media: Polypropylene Melt-blown

Weight: 15g +- 5g each Nose Flange: **PU Foam** 

of manufacture when stored within the temperature range of -5°C to +50°C and less than 80% relative humidity.

use, always check that the product is within the stated shelf life. When storing or transporting this product use original packaging provided.

Ensure disposable mask is correctly fitted prior to each use and conduct annual fit testing in accordance with AS/NZS 1715:2009.

# **WARNINGS AND USE LIMITATIONS**

- Facial hair has the potential to compromise the required protective seal of the respirator
- Ensure adequate oxygen levels are present
- Ensure the contamination is known and the respirator is suitable for the application
- Replace when taste, smell or the breathing resistance is high
- Store in a clean, resealable storage device

### **STANDARDS**

#### **CERTIFIED TO:**

AS/NZS 1716:2012 Respiratory Protective Devices

Certified by Benchmark

Identification number: BMP547903

To be used in conjunction with:

AS/NZS 1715:2009 Selection, Use and Maintenance of Respiratory **Protective Equipment** 

CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES	
P1	80% (Particles to 1μm micron = 0.001mm size)	Dust	
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes	
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only	

# **CARE INSTRUCTIONS** Shelf life of the unopened product is three (3) years from date End of shelf life date is marked on the product packaging. Before initial

### RELATED PRODUCTS

PRODUCT CODE:



**DUST MASKS P2** 

PRODUCT CODE:



**DUST MASKS FLAT FOLD** 

PRODUCT CODE:



DUST MASKS PROMESH

PRODUCT CODE:



DUST MASKS PROMESH P2 + VALVE + CARBON

PRODUCT CODE:



MAXI MASK 2000 HALF MASK RESPIRATOR **BODY ONLY** 

AUSTRALIA: 1800 770 723

**NEW ZEALAND:** 0800 770 723 NZ@PARAMOUNTSAFETY.CO.NZ ADELAIDE: (613) 9764 9900 SA@PARAMOUNTSAFETY.COM.AU

RRISRANE. (617) 3806 2699 QLD@PARAMOUNTSAFETY.COM.AU

MELBOURNE: (613) 9764 9900 VIC@PARAMOUNTSAFETY.COM.AU

(618) 9301 7888 WA@PARAMOUNTSAFETY.COM.AU

(612) 9601 3877 NSW@PARAMOUNTSAFETY.COM.AU



